

Deluxe  
group B

Note: Photographic fabric scans are not colour accurate.  
Always request actual fabric samples before ordering.



108



109



110




112



111



60




6



119




4



115




183



184



122



258




162



9



161



188



207



120



118



2



101

# Deluxe

## Product information

Deluxe has a unique velvety touch and durability which makes it preferable for all types of soft seating. Fabric Deluxe is suitable for a wide variety of interiors with its easy-to-use nature and cosy feeling. The colour concept of Deluxe is created to reflect both earth and nature tones and the shades of sky.

## Technical information

| EN                                                  | D                                                    | F                                                              | ES                                                     |
|-----------------------------------------------------|------------------------------------------------------|----------------------------------------------------------------|--------------------------------------------------------|
| Composition<br>100% Polyester                       | Zusammensetzung<br>100% Polyester                    | Composition<br>100% Polyester                                  | Composición<br>100% Poliéster                          |
| Width<br>140 cm                                     | Breite<br>140 cm                                     | Largeur<br>140 cm                                              | Ancho<br>140 cm                                        |
| Weight<br>480 gr/m2                                 | Gewicht<br>480 gr/m2                                 | Poids<br>480 gr/m2                                             | Peso<br>480 gr/m2                                      |
| Abrasion Resistance<br>25,000 Martindale Cycle      | Scheuerfestigkeit<br>25,000 Martindale Fahrräder     | Résistance à l'abrasion<br>25,000 Martindale Cycle             | Resistencia a la abrasión<br>25,000 Martindale Ciclos  |
| Pilling<br>>5 (GRI 5000 ISO 12945)                  | Pilling<br>>5 (GRI 5000 ISO 12945)                   | Boulochage<br>>5 (GRI 5000 ISO 12945)                          | Pilling<br>>5 (GRI 5000 ISO 12945)                     |
| Color Fastness<br>>5 (ISO 105X12)                   | Farbechtheit<br>>5 (ISO 105X12)                      | Solidité de la couleur<br>>5 (ISO 105X12)                      | Rapidez del color<br>>5 (ISO 105X12)                   |
| Washing Shrinkage<br>>1%                            | Waschschrumpfung<br>>1%                              | Retrait de lavage<br>>1%                                       | Contracción de lavado<br>>1%                           |
| Color Fastness to Light<br>>4/5 (XENON ISO 105 B02) | Farbechtheit gegen Licht<br>>4/5 (XENON ISO 105 B02) | Solidité des couleurs à la lumière<br>>4/5 (XENON ISO 105 B02) | Solidez del color a la luz<br>>4/5 (XENON ISO 105 B02) |