

Divina
group E

Divina Melange 2
group E



220



260



280



920



421



721



821



871



771




180



521



531



620



671



631

Divina MD
group E



203



213



613



913



453



433



633



653



683



753



813



843



873



743



733

Note: Photographic fabric scans are not colour accurate.
Always request actual fabric samples before ordering.

Divina 3
group E



106



224



426



536



542



562



636



662



696



671



712



826



836



893



791



936



956



922



756



782



171




173



154



181




691




346



356



393



384



191

Divina 3 / Divina Melange 2 / Divina MD

Product information

Divina upholstery family is available in sophisticated and rich colours. Thanks to its smooth and consistent surface, it complements the shape of furniture very well.

This fabric family is quite suitable for soft seating for both contract and private use and fabrics complement each other perfectly. The colour concept of Divina family is designed to capture all shades of oil paintings . As the fabrics show off the colours in all their glory, a dramatic and dynamic atmosphere can be created within the overall furniture scheme.

Technical information

EN	D	F	ES
Composition 100% New Wool	Zusammensetzung 100% Schurwolle	Composition 100% Laine Vierge	Composición 100% Lana Virgen
Yarn type Staple	Garntyp Faser	Type de fil Fibre	Tipo de hilo Fibra
Width 150 cm	Breite 150 cm	Largeur 150 cm	Ancho 150 cm
Weight Divina 3: 560 gr/m2 Divina Melange 2 & Divina MD: Approximately 820 g/lin.m	Gewicht Divina 3: 560 gr/m2 Divina Melange 2 & Divina MD: Ca. 820 g/lin.m	Poids Divina 3: 560 gr/m2 Divina Melange 2 & Divina MD: Approximativement 820 g/lin.m	Peso Divina 3: 560 gr/m2 Divina Melange 2 & Divina MD: Aproximadamente 820 g/lin.m
Flammability EN 1021-1/2 BS 5852, ignition source 2-5 DIN 4102 B2 Önorm B1/Q1 NF D 60 013 UNI 9175, 1IM Cal. Tech. Bull. 117, Sec. E IMO A.652(16)	Feuersicherung EN 1021-1/2 BS 5852, zündquelle 2-5 DIN 4102 B2 Önorm B1/Q1 NF D 60 013 UNI 9175, 1IM Cal. Tech. Bull. 117, Sec. E IMO A.652(16)	Flammabilité EN 1021-1/2 BS 5852, source d'inflammation 2-5 DIN 4102 B2 Önorm B1/Q1 NF D 60 013 UNI 9175, 1IM Cal. Tech. Bull. 117, Sec. E IMO A.652(16)	Inflamabilidad EN 1021-1/2 BS 5852, fuente de ignición 2-5 DIN 4102 B2 Önorm B1/Q1 NF D 60 013 UNI 9175, 1IM Cal. Tech. Bull. 117, Sec. E IMO A.652(16)
Light Fastness Note 5-7 (ISO 105-B02)	Lichtechtheit Note 5-7 (ISO 105-B02)	Solidité à la lumière Note 5-7 (ISO 105-B02)	Solidez a la luz Note 5-7 (ISO 105-B02)
Pilling Note 3 (EN ISO 12945)	Pilling Note 3 (EN ISO 12945)	Boulochage Note 3 (EN ISO 12945)	Pilling Note 3 (EN ISO 12945)
Abasion Resistance Divina 3: 45,000 Martindale Cycle (EN ISO 12947) Divina Melange 2 / Divina MD: Approximately 45.000 Martindale, EN ISO 12947	Scheuerfestigkeit Divina 3: 45,000 Martindale Fahrräder (EN ISO 12947) Divina Melange 2 / Divina MD: Ca. 45.000 Martindale, EN ISO 12947	Résistance à l'abrasion Divina 3: 45,000 Martindale Cycle (EN ISO 12947) Divina Melange 2 / Divina MD: Approximativement 45.000 Martindale, EN ISO 12947	Resistencia a la abrasión Divina 3: 45,000 Martindale Ciclos (EN ISO 12947) Divina Melange 2 / Divina MD: Aproximadamente 45.000 Martindale, EN ISO 12947
Cleaning Dry cleaning or clean with foam detergents.	Reinigung Chemische Reinigung oder Reinigung mit Schaummittel.	Nettoyage Nettoyage à sec ou nettoyage avec des détergents en mousse.	Limpieza Limpieza en seco o limpieza con detergentes de espuma.